
| Bulletin | UK | Export | Issued |
|----------|-----|--------|-----------|
| 1388 | YES | YES | 23/7/2018 |

R65 LED Warning Beacons

Vapormatic's new range of ECE Regulation 65 approved LED warning beacons are suitable for highways maintenance, roadside works or inspection. Manufactured with a tough, durable plastic body and impact-resistant polycarbonate lens, this range of versatile beacons are suitable for a wide range of applications; Agricultural, Commercial and Industrial.



All beacons in this range feature:

- 8 x High intensity LED's
- 3 x flash patterns - 360° rotation, low and high-speed strobe
- Suitable for 12v or 24v vehicles
- 4 mounting options available
- Reg 65 Highways maintenance approved
- IP66 rated, 'E' approved and 'CE' certified




The compact 'boule-type' styling is designed to create a low profile and help minimize overall vehicle height, which is particularly useful with larger agricultural and commercial vehicles or sites with overhead obstructions or hazards.

All light beacons feature high intensity LED's with a very low current draw for low power consumption, higher light intensity longer working life and better use of available, stored vehicle battery energy.

Part No: [VLC6155](#)

Low profile, flexi-pole DIN mount LED beacon

ECE Reg 65 highways maintenance approved LED warning beacon. Flexi DIN pole mount takes seconds to change - simply unscrew the wingnut on the DIN stem and unplug to remove! Low profile 'boule' styling – just 174mm high! Manufactured from tough plastic with an impact-resistant polycarbonate lens. 2 selectable flash patterns - 360° rotational flash and strobe. E-marked. 12-24V.



- Measurements: Width 127mm; Height 174mm.
- High intensity 8 x LED module
- Very low power consumption
- Modern low-profile design
- Reverse polarity protection
- IP66 rated – dust & water protection
- Operating temperature -30°C + 50°C
- Can be used on either 12V or 24V vehicles.




| Bulletin | UK | Export | Issued |
|----------|-----|--------|-----------|
| 1388 | YES | YES | 23/7/2018 |

Part No: [VLC6152](#)

Low profile, magnetic mount LED beacon

ECE Reg 65 highways maintenance approved LED warning beacon. Strong magnetic base mount tested to 70mph (112kph). Low profile 'boule' styling – just 135mm high! Manufactured from tough plastic with a rubber base and an impact-resistant polycarbonate lens. 2 selectable flash patterns - 360° rotational flash and strobe. Cigar lighter adaptor (2.5m length) with control switches. E-marked. 12-24V.




- Measurements: Width 140mm; Height 135mm.
- High intensity 8 x LED module
- Very low power consumption
- Modern low-profile design
- Reverse polarity protection
- IP66 rated – dust & water protection
- Operating temperature -30°C + 50°C
- Can be used on either 12V or 24V vehicles.

Part No: [VLC6153](#)

Low profile, 3 bolt mount LED Beacon

ECE Reg 65 highways maintenance approved LED warning beacon. Surface mount, three bolt fitting. Low profile 'boule' styling – just 135mm high! Manufactured from tough plastic with a rubber base and an impact-resistant polycarbonate lens. 2 selectable flash patterns - 360° rotational flash and strobe. E-marked. 12-24V.




- Measurements: Width 140mm; Height 135mm.
- High intensity 8 x LED module
- Very low power consumption
- Modern low-profile design
- Reverse polarity protection
- IP66 rated – dust & water protection
- Operating temperature -30°C + 50°C
- Can be used on either 12V or 24V vehicles.

| Bulletin | UK | Export | Issued |
|----------|-----|--------|-----------|
| 1388 | YES | YES | 23/7/2018 |


Part No: [VLC6154](#)

Low profile, 1 bolt mount LED beacon

ECE Reg 65 highways maintenance approved LED warning beacon. Single stainless steel hollow bolt mount fitting to conceal wiring for a clean installation. Low profile 'boule' styling – just 130mm high! Manufactured from tough plastic base with an impact-resistant polycarbonate lens. 2 selectable flash patterns - 360° rotational flash and strobe. E-marked. 12-24V.



- Measurements: Width 127mm; Height 130mm.
- High intensity 8 x LED module
- Very low power consumption
- Modern low-profile design
- Reverse polarity protection
- IP66 rated – dust & water protection
- Operating temperature -30°C + 50°C
- Can be used on either 12V or 24V vehicles

| | |
|---|--|
| <p>Canbus LED Resistor</p> | <p>Part No: VLC2361</p> |
|  | <p>Helps eliminate Canbus errors and fault codes with this LED resistor. With easy installation this product offers a convenient solution when converting to LED lighting.</p> |



All Vapormatic quality replacement parts carry an industry leading **12 month parts and labour warranty**. For further information on specific items please visit www.vapormatic.com